



B6 Blender and Freezer

Specifications and Installation Requirements



B6 BLENDER

Self-Sanitizing
(Blender only, sold separately)



BLENDING BAR

Our Best Selling Blender
& Freezer Configuration



MINI BLENDING BAR

Good for Medium Traffic
Smaller Footprint



DOUBLE BLENDING BAR

Allows for Dual Blending
Supports High Foot Traffic



SINGLE DOOR FREEZER

Best Selling Blender
and Compact Freezer
Left hinge option is also available



SINGLE DOOR FREEZER

Best Selling Blender
and Compact Freezer
Left hinge option is also available



TALL UPRIGHT FREEZER

Highest Cup Capacity
Good for Limited Storage
Left hinge option is also available



SIDE COUNTER

Optional Storage
(Sold Separately)

Freezer & Equipment Specifications

Freezer	W"	D"	H"	Cup Capacity	Facings	Empty Weight	Full Weight	Shipping Dimensions
MINI BLENDING BAR	33.5"	32.5"	56"	90	15	225 LBS	295 LBS	37.5 x 37.5 x 67"
BLENDING BAR	45.5"	32.5"	56"	180	30	245 LBS	385 LBS	38 x 40 x 62"
DOUBLE BLENDING BAR	61.5"	32.5"	56"	180	30	250 LBS	390 LBS	38 x 40 x 62"
SINGLE DOOR FREEZER (COUNTERTOP - LEGS)	28"	31"	32.6"	102	18	200 LBS	280 LBS	37 x 35 x 40"
SINGLE DOOR FREEZER (UNDERCOUNTER - CASTERS)	28"	31"	32.25"	102	18	200 LBS	280 LBS	37 x 35 x 40"
TALL UPRIGHT FREEZER	30"	29.5"	78.5"	252	42	365 LBS	560 LBS	36 x 38 x 84"
SIDE COUNTER	16"	26"	36"	-	-	-	-	34 x 25 x 42"

NOTE: Blending Bar dimensions include blender(s). Please confirm available space prior to ordering.
Blender & Freezer price does not include applicable taxes or shipping & handling.

Blender Specs*

DIMENSIONS: 15.25" W / 25" D / 42" H

WEIGHT: 125 LBS

CERTIFICATIONS: NSF, TÜV, SUD

*Add the dimensions of desired freezer to the dimensions of the blender when planning for necessary equipment space.

Power

- Dedicated 120V, 60Hz, 15A circuit
- 7 FT grounded power cord (included)
- Freezer requires separate dedicated 120V, 60Hz, 15A circuit

Water

- Water supply filtered to 120 ppm hardness and 150 ppm TDS
- Minimum supplied water pressure of 25 PSI
- Maximum supplied water pressure of 50 PSI
- 3/8" ID braided water supply line to blender (not included)

Drain

- Gravity drain setup required
- 9 FT of 3/4" ID corrugated drain tube (included)

NOTE: Failure to follow requirements may impact warranty coverage.

FOR MORE INFORMATION, CONTACT SALES@FREAL.COM