

# **B6 BLENDER AND FREEZER**

## SPECIFICATIONS AND INSTALLATION REQUIREMENTS



### **B6 BLENDER**

Self-Sanitizing (Blender only, sold separately)

FR00-0106



## SINGLE DOOR FREEZER

Best Selling Blender and Compact Freezer

Left hinge option is also available

FR10-0007-RHL



#### **BLENDING BAR**

Our Best Selling Blender & Freezer Configuration

FR10-0011



## SINGLE DOOR FREEZER

Best Selling Blender and Compact Freezer

Left hinge option is also available

FR10-0007-RHC



#### MINI BLENDING BAR

Good for Medium Traffic Smaller Footprint

FR10-0011-M



### DOUBLE BLENDING BAR

Allows for Dual Blending Supports High Foot Traffic

FR10-0011-DH



## TALL UPRIGHT FREEZER

Highest Cup Capacity Good for Limited Storage

Left hinge option is also available

FR10-0022-RH



## SIDE COUNTER

**Optional Storage** (Sold Separately)

FR10-SCTR

## FREEZER PRICES & EQUIPMENT SPECIFICATIONS

FREEZER	W"	D"	Н"	CUP	FACINGS	EMPTY WEIGHT	FULL WEIGHT
MINI BLENDING BAR	33.5"	32.5"	56"	90	15	225 LBS	295 LBS
BLENDING BAR	45.5"	32.5"	56"	180	30	245 LBS	385 LBS
DOUBLE BLENDING BAR	61.5"	32.5"	56"	180	50	250 LBS	390 LBS
SINGLE DOOR FREEZER (COUNTERTOP - LEGS)	28"	31"	32.6"	102	18	200 LBS	280 LBS
SINGLE DOOR FREEZER (UNDERCOUNTER - CASTERS)	28"	31"	32.25"	102	18	200 LBS	280 LBS
TALL UPRIGHT FREEZER	30"	29.5"	78.5"	252	42	365 LBS	560 LBS
SIDE COUNTER	16"	26"	36"	-	-	-	-

NOTE: Blending Bar dimensions include blender(s). Please confirm available space prior to ordering Blender & Freezer price does not include applicable taxes or shipping & handling.

#### **BLENDER SPECS\***

**DIMENSIONS:** 15.25" W / 25" D / 42" H

CERTIFICATIONS: NSF, TÜV, SUD

\*Add the dimensions of desired freezer to the dimensions of the blender when planning for necessary equipment space.

#### **POWER**

- Dedicated 120V. 60Hz. 15A circuit
- 7 FT grounded power cord (included)
- Freezer requires separate dedicated 120V. 60Hz. 15A circuit

#### WATER

- Water supply filtered to 120 ppm hardness and 150 ppm TDS
- Minimum supplied water pressure of 25 PSI · Maximum supplied water pressure of 50 PSI
- 3/8" ID braided water supply line to blender (not included)

#### DRAIN

- · Gravity drain setup required
- 9 FT of 3/4" ID corrugated drain tube (included)

NOTE: Failure to follow requirements may impact warranty coverage